


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm		
NAME: REG2095RF-20E30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:85	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 78.44 lm/W
MODEL	3000K CRI80	I <sub>max</sub> (cd)	11555	S/MH(C0/180)	0.31	
NOMINAL POWER(W)	20	LOR(%)	100.0	S/MH(C90/270)	0.33	
RATED VOLTAGE(V)	226	TOTAL FLUX(lm)	1553.2	η UP,DN(C0-180)	0.0,48.8	
NOMINAL FLUX(lm)	1553.16	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,51.2	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.00	
TEST VOLTAGE(V)	225.2	η down(%)	100.0	CIBSE SHR MAX	1.00	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:AE  
 Test Date:2020-04-03

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity:65.0%  
 Test Distance:7.240m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
10	531.4	526.9	499.4	497.1	503.9	514.9	547.1	537.4	0- 10	749.4	749.4	48.2, 48.2
20	82.04	75.32	64.49	66.41	70.15	71.57	84.84	85.01	10- 20	689.6	1439	92.6, 92.6
30	5.487	5.543	5.344	5.301	5.340	5.361	5.584	5.375	20- 30	88.10	1527	98.3, 98.3
40	1.099	1.132	1.074	1.074	1.108	1.088	1.102	1.104	30- 40	18.50	1546	99.5, 99.5
50	0.2471	0.2503	0.2278	0.2271	0.2588	0.2611	0.2804	0.2863	40- 50	4.736	1550	99.8, 99.8
60	0.0390	0.0245	0.0295	0.0327	0.0604	0.0622	0.0617	0.0730	50- 60	1.154	1551	99.9, 99.9
70	0.0253	0.0286	0.0290	0.0294	0.0545	0.0543	0.0530	0.0506	60- 70	0.2978	1552	99.9, 99.9
80	0.0665	0.0700	0.0686	0.0722	0.0658	0.0676	0.0686	0.0663	70- 80	0.5949	1552	99.9, 99.9
90	0.1055	0.1055	0.1066	0.1070	0.0366	0.0387	0.0388	0.0404	80- 90	0.7984	1553	100, 100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY: $\times 10\text{cd}$									UNIT: lm		

Conical surface Flux(90deg): 1548.7 lm

%lum = 99.7%

%lamp = 99.7%

Conical surface Flux(120deg): 1551.5 lm

%lum = 99.9%


%lamp = 99.9%

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: AE  
 Test Date: 2020-04-03

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity: 65.0%  
 Test Distance: 7.240m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm		
NAME: REG2095RF-20E30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:85	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1756	1898
80	679	695
75	298	317
70	131	149
65	63	65
60	138	104
55	353	300
50	681	624
45	1473	1411


C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-04-03

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm		
NAME: REG2095RF-20E30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:85	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.14	1.12	1.10	1.11	1.10	1.09	1.08	1.06	1.05	1.04	1.03	1.02	1.01	.00	.99	.98
2.0	1.09	1.06	1.04	1.07	1.05	1.03	1.04	1.02	1.01	1.02	1.00	.99	.99	.98	.97	.95
3.0	1.05	1.02	.00	1.04	1.01	.99	1.02	.99	.97	.99	.97	.96	.97	.96	.94	.93
4.0	1.02	.99	.96	1.01	.98	.95	.99	.96	.94	.97	.95	.93	.96	.94	.92	.91
5.0	.99	.96	.93	.98	.95	.93	.97	.94	.92	.95	.93	.91	.94	.92	.90	.89
6.0	.96	.93	.90	.96	.93	.90	.95	.92	.90	.93	.91	.89	.92	.90	.88	.88
7.0	.94	.91	.88	.94	.90	.88	.93	.90	.88	.92	.89	.87	.91	.88	.87	.86
8.0	.92	.89	.86	.92	.88	.86	.91	.88	.86	.90	.87	.85	.89	.87	.85	.84
9.0	.90	.87	.84	.90	.86	.84	.89	.86	.84	.88	.86	.84	.88	.85	.83	.83
10.0	.88	.85	.83	.88	.85	.83	.87	.84	.82	.87	.84	.82	.86	.84	.82	.81



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:AE  
 Test Date:2020-04-03

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity:65.0%  
 Test Distance:7.240m [K=1.0000]  
 Remarks:

### WEC AND CCEC

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm					
NAME: REG2095RF-20E30-S			TYPE:		WEIGHT:
SPEC.:			DIM.:		SERIAL No.:
MFR.:			SUR.:85		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.124	.070	.022	.117	.067	.021	.105	.060	.019	.093	.054	.017	.083	.048	.016	
2.0	.113	.062	.019	.107	.059	.018	.097	.054	.017	.088	.049	.015	.079	.045	.014	
3.0	.104	.055	.017	.099	.053	.016	.091	.049	.015	.083	.046	.014	.076	.042	.013	
4.0	.096	.050	.015	.093	.049	.014	.086	.045	.014	.079	.043	.013	.073	.040	.012	
5.0	.090	.046	.013	.087	.045	.013	.081	.042	.012	.076	.040	.012	.071	.038	.011	
6.0	.085	.042	.012	.082	.041	.012	.077	.039	.011	.072	.038	.011	.068	.036	.011	
7.0	.080	.040	.011	.078	.039	.011	.073	.037	.011	.069	.036	.010	.066	.034	.010	
8.0	.076	.037	.010	.074	.036	.010	.070	.035	.010	.067	.034	.010	.063	.033	.009	
9.0	.072	.035	.010	.071	.034	.010	.067	.033	.009	.064	.032	.009	.061	.031	.009	
10.0	.069	.033	.009	.068	.033	.009	.065	.032	.009	.062	.031	.009	.059	.030	.009	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.167	.158	.149	.143	.135	.128	.098	.093	.089	.056	.054	.052	.018	.017	.017	
2.0	.148	.133	.120	.127	.114	.103	.087	.079	.072	.050	.046	.042	.016	.015	.014	
3.0	.132	.113	.098	.114	.098	.085	.078	.068	.059	.045	.040	.035	.014	.013	.011	
4.0	.119	.098	.081	.102	.084	.070	.070	.059	.050	.041	.034	.029	.013	.011	.010	
5.0	.108	.085	.068	.093	.074	.059	.064	.051	.042	.037	.030	.025	.012	.010	.008	
6.0	.099	.075	.058	.085	.065	.050	.058	.045	.036	.034	.027	.021	.011	.009	.007	
7.0	.091	.066	.049	.078	.058	.043	.054	.040	.031	.031	.024	.018	.010	.008	.006	
8.0	.084	.059	.043	.072	.052	.037	.050	.036	.026	.029	.021	.016	.009	.007	.005	
9.0	.078	.054	.037	.067	.046	.032	.046	.033	.023	.027	.019	.014	.009	.006	.005	
10.0	.073	.049	.033	.063	.042	.029	.043	.030	.020	.025	.018	.012	.008	.006	.004	

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-04-03

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm											
NAME: REG2095RF-20E30-S					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.:85			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H		-1.3	-0.7	-1.1	-0.6	-0.4	-1.5	-1.0	-1.3	-0.8	-0.7
	3H	-1.4	-0.9	-1.2	-0.7	-0.5	-1.6	-1.1	-1.4	-0.9	-0.7
	4H	-1.4	-0.9	-1.2	-0.7	-0.5	-1.6	-1.1	-1.4	-0.9	-0.7
	6H	-1.2	-0.8	-0.9	-0.5	-0.3	-1.4	-0.9	-1.1	-0.7	-0.5
	8H	-0.9	-0.5	-0.7	-0.2	0.0	-1.1	-0.6	-0.8	-0.4	-0.2
	12H	-0.4	0.0	-0.1	0.3	0.6	-0.5	-0.0	-0.2	0.2	0.5
4H	2H	-1.5	-1.0	-1.2	-0.8	-0.6	-1.7	-1.2	-1.5	-1.0	-0.8
	3H	-1.6	-1.2	-1.3	-0.9	-0.7	-1.8	-1.4	-1.5	-1.1	-0.9
	4H	-1.6	-1.2	-1.3	-0.9	-0.6	-1.8	-1.4	-1.5	-1.1	-0.8
	6H	-1.2	-0.8	-0.8	-0.5	-0.2	-1.4	-1.0	-1.0	-0.7	-0.4
	8H	-0.7	-0.4	-0.3	-0.0	0.3	-0.8	-0.5	-0.4	-0.1	0.2
	12H	0.2	0.5	0.6	0.9	1.2	0.2	0.5	0.6	0.9	1.2
8H	4H	-1.6	-1.3	-1.3	-1.0	-0.6	-1.8	-1.5	-1.5	-1.2	-0.8
	6H	-1.0	-0.7	-0.6	-0.3	0.1	-1.1	-0.9	-0.7	-0.5	-0.1
	8H	-0.2	0.0	0.2	0.4	0.9	-0.3	-0.1	0.1	0.4	0.8
	12H	1.0	1.3	1.5	1.7	2.2	1.1	1.3	1.5	1.7	2.2
12H	4H	-1.6	-1.3	-1.2	-0.9	-0.6	-1.8	-1.5	-1.4	-1.1	-0.8
	6H	-0.9	-0.6	-0.4	-0.2	0.2	-1.0	-0.8	-0.6	-0.3	0.1
	8H	0.0	0.3	0.5	0.7	1.2	-0.0	0.2	0.4	0.6	1.1
Variations with the observer position at spacings:											
S = 1.0H		+ 1.8 / - 1.7				+ 1.6 / - 1.6					
1.5H		+ 3.3 / - 1.6				+ 3.0 / - 1.5					
2.0H		+ 1.9 / - 0.7				+ 1.8 / - 0.6					

CIE Pub.117, 1553 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.5)

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-04-03

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm		
NAME: REG2095RF-20E30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:85	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	91	86	82	91	85	82	90	85	82	79
0.80	98	93	90	98	93	90	96	92	89	86
1.00	102	97	94	101	96	93	100	96	93	89
1.25	105	101	98	104	100	97	103	99	97	93
1.50	108	104	101	107	103	100	104	101	99	95
2.00	110	106	103	109	105	103	106	103	101	96
2.50	111	108	105	110	107	104	107	104	102	97
3.00	113	110	107	111	108	106	108	106	104	98
4.00	115	112	110	113	110	109	109	107	106	99
5.00	116	114	112	114	112	111	110	109	107	100
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-04-03

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm		
NAME: REG2095RF-20E30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:85	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-04-03

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm		
NAME: REG2095RF-20E30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:85	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-04-03

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

# ISOLUX DIAGRAM

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm		
NAME: REG2095RF-20E30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:85	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:AE  
Test Date:2020-04-03

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity:65.0%  
Test Distance:7.240m [K=1.0000]  
Remarks:

## LED Avg.L Report

Test:U:225.2V I:0.0920A P:19.80W PF:0.9510 Freq:50.00Hz Lamp Flux:1553.16x1 lm		
NAME: REG2095RF-20E30-S	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:85	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	113
L_0~180 (75) av	364
L_0~180 (85) av	1443
L_90~270 (65) av	113
L_90~270 (75) av	379
L_90~270 (85) av	1517
L_45 (65) av	110
L_45 (75) av	390
L_45 (85) av	1526

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:AE  
 Test Date:2020-04-03

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
 Humidity:65.0%  
 Test Distance:7.240m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: AE  
Test Date: 2020-04-03

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.265  
Humidity: 65.0%  
Test Distance: 7.240m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.265
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```