


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 79.43 lm/W			
MODEL	ALT85-42G30-45	I _{max} (cd)	5683	S/MH(C0/180)	0.68
NOMINAL POWER(W)	42	LOR(%)	100.0	S/MH(C90/270)	0.68
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	3335.9	□ UP,DN(C0-180)	0.0,50.2
NOMINAL FLUX(lm)	3335.87	CIE CLASS	DIRECT	□ UP,DN(C180-360)	0.0,49.8
LAMPS INSIDE	1	□ up(%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE(V)	225	□ down(%)	100.0	CIBSE SHR MAX	0.65

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: AE
 Test Date: 2020-03-06

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 7.240m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	4929	4963	4956	4985	4981	4957	4962	4944	0- 10	505.6	505.6	15.2,15.2
20	3323	3374	3313	3395	3399	3376	3418	3325	10- 20	1191	1697	50.9,50.9
30	1245	1282	1275	1293	1284	1231	1235	1210	20- 30	960.4	2657	79.7,79.7
40	425.5	436.9	431.6	433.4	426.8	407.6	421.5	421.4	30- 40	487.8	3145	94.3,94.3
50	62.67	63.76	61.16	61.53	60.87	59.83	62.94	63.28	40- 50	143.4	3288	98.6,98.6
60	18.58	16.76	15.29	15.02	15.85	16.34	16.97	17.99	50- 60	28.47	3317	99.4,99.4
70	7.757	7.431	6.872	6.992	7.240	7.399	7.712	7.846	60- 70	11.43	3328	99.8,99.8
80	2.579	2.659	2.561	2.597	2.280	2.269	2.303	2.280	70- 80	5.029	3333	99.9,99.9
90	3.245	3.216	3.198	3.220	2.375	2.363	2.372	2.362	80- 90	2.693	3336	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-03-06

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-03-06

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm					
NAME:		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.:75		Shielding Angle:	

<input type="checkbox"/> cc	80%			70%			50%			30%			10%			0
<input type="checkbox"/> w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
<input type="checkbox"/> fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.168	.095	.030	.161	.092	.029	.148	.085	.027	.137	.079	.025	.126	.073	.024	
2.0	.159	.087	.027	.153	.085	.026	.143	.079	.025	.133	.075	.023	.124	.070	.022	
3.0	.151	.080	.024	.146	.078	.024	.137	.074	.023	.129	.071	.022	.121	.067	.021	
4.0	.143	.074	.022	.139	.073	.022	.131	.070	.021	.124	.067	.020	.118	.064	.019	
5.0	.136	.069	.020	.133	.068	.020	.126	.066	.019	.120	.063	.019	.114	.061	.018	
6.0	.130	.065	.019	.127	.064	.018	.121	.062	.018	.116	.060	.018	.110	.058	.017	
7.0	.124	.061	.017	.121	.060	.017	.116	.059	.017	.111	.057	.017	.107	.056	.016	
8.0	.119	.058	.016	.116	.057	.016	.112	.056	.016	.107	.054	.016	.103	.053	.015	
9.0	.114	.055	.015	.112	.054	.015	.108	.053	.015	.104	.052	.015	.100	.051	.015	
10.0	.109	.052	.015	.107	.052	.014	.104	.051	.014	.100	.050	.014	.097	.049	.014	

<input type="checkbox"/> cc	80%			70%			50%			30%			10%			0
<input type="checkbox"/> w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
<input type="checkbox"/> fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.157	.146	.146	.135	.125	.100	.093	.087	.057	.054	.050	.018	.017	.016	
2.0	.155	.133	.114	.132	.114	.099	.091	.079	.069	.052	.046	.040	.017	.015	.013	
3.0	.142	.113	.091	.121	.098	.079	.083	.068	.055	.048	.040	.033	.015	.013	.011	
4.0	.131	.099	.074	.112	.085	.064	.077	.059	.045	.045	.035	.027	.014	.011	.009	
5.0	.122	.087	.061	.104	.075	.053	.072	.052	.038	.042	.031	.022	.013	.010	.007	
6.0	.114	.077	.051	.098	.067	.045	.068	.047	.032	.039	.028	.019	.013	.009	.006	
7.0	.107	.070	.043	.092	.060	.038	.064	.042	.027	.037	.025	.016	.012	.008	.005	
8.0	.101	.063	.037	.087	.055	.032	.060	.039	.023	.035	.023	.014	.011	.007	.005	
9.0	.096	.058	.032	.083	.050	.028	.057	.035	.020	.033	.021	.012	.011	.007	.004	
10.0	.092	.054	.028	.079	.047	.025	.055	.033	.018	.032	.019	.010	.010	.006	.003	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm												
NAME:					TYPE:			WEIGHT:				
SPEC.:					DIM.:			SERIAL No.:				
MFR.:					SUR.:75			Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3		
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3		
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2		
Room dimensions	Viewed crosswise					Viewed endwise						
x = 2H y = 2H	2H	17.2	18.0	17.4	18.2	18.4	17.3	18.1	17.5	18.3	18.5	
	3H	17.0	17.8	17.3	18.0	18.2	17.1	17.9	17.4	18.1	18.3	
	4H	17.0	17.7	17.2	17.9	18.2	17.1	17.8	17.3	18.0	18.3	
	6H	16.9	17.6	17.2	17.8	18.1	17.0	17.7	17.3	17.9	18.2	
	8H	16.8	17.5	17.2	17.8	18.0	16.9	17.6	17.2	17.9	18.1	
	12H	16.8	17.5	17.1	17.7	18.0	16.9	17.6	17.2	17.8	18.1	
	4H	2H	16.9	17.7	17.2	17.9	18.1	17.0	17.8	17.3	18.0	18.2
		3H	16.8	17.5	17.1	17.7	18.0	16.9	17.6	17.2	17.8	18.1
		4H	16.7	17.3	17.1	17.6	17.9	16.8	17.4	17.2	17.7	18.0
		6H	16.7	17.2	17.0	17.5	17.9	16.7	17.3	17.1	17.6	17.9
		8H	16.6	17.1	17.0	17.4	17.8	16.7	17.2	17.1	17.5	17.9
		12H	16.6	17.0	17.0	17.4	17.8	16.7	17.1	17.1	17.5	17.9
8H	4H	16.6	17.1	17.0	17.4	17.8	16.7	17.2	17.1	17.5	17.9	
	6H	16.5	16.9	16.9	17.3	17.7	16.6	17.0	17.0	17.4	17.8	
	8H	16.5	16.8	16.9	17.2	17.7	16.6	16.9	17.0	17.3	17.8	
	12H	16.5	16.8	16.9	17.2	17.7	16.5	16.8	17.0	17.3	17.8	
12H	4H	16.5	17.0	17.0	17.4	17.7	16.6	17.1	17.0	17.5	17.8	
	6H	16.5	16.8	16.9	17.2	17.7	16.6	16.9	17.0	17.3	17.8	
	8H	16.4	16.7	16.9	17.2	17.6	16.5	16.8	17.0	17.3	17.7	
Variations with the observer position at spacings:												
S = 1.0H	+ 2.9 / - 9.4					+ 3.0 / - 9.7						
1.5H	+ 5.2 / - 8.4					+ 5.3 / - 8.6						
2.0H	+ 5.4 / - 3.8					+ 5.8 / - 4.1						

CIE Pub.117, 3336 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 4.2$)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	88	82	78	87	82	78	87	81	78	74
0.80	95	90	86	95	89	86	94	89	85	82
1.00	100	94	91	99	94	90	97	94	90	86
1.25	104	99	95	103	98	95	101	97	94	90
1.50	106	102	98	105	101	98	103	99	97	92
2.00	109	105	102	107	104	101	105	102	99	94
2.50	110	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	96
4.00	114	111	109	112	110	108	108	106	105	98
5.00	115	113	111	113	111	110	109	108	106	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: AE
 Test Date: 2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 7.240m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

AAI Figure

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:224.9V I:0.1920A P:42.00W PF:0.9700 Freq:50.00Hz Lamp Flux:3335.87x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	6050
L_0~180 (75) av	4190
L_0~180 (85) av	6281
L_90~270 (65) av	5968
L_90~270 (75) av	4100
L_90~270 (85) av	6268
L_45 (65) av	5984
L_45 (75) av	4142
L_45 (85) av	6283

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: AE
Test Date: 2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 7.240m [K=1.0000]
Remarks:

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```